

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1	"5602422".pn.	USPAT; EPO; JPO	OR	ON	2005/06/29 10:34
L2	1	"5829988".pn.	USPAT; EPO; JPO	OR	ON	2005/06/29 10:42
L3	16	(resilient sping\$3) near3 (conduct\$3 metal\$3 spring pin) with treat\$4 and (heat\$4 air\$3 gas\$4 ag\$4) near4 (treat\$4 harden\$3) and (contact pad land) with (trace line)	USPAT; EPO; JPO	OR	ON	2005/06/29 10:47
L4	14	(resilient sping\$3) near3 (conduct\$3 metal\$3 spring pin) with (contact pad land) with (trace line) and (heat\$4 air\$3 gas\$4 ag\$4) near4 (treat\$4 harden\$3)	USPAT; EPO; JPO	OR	ON	2005/06/29 10:49
L6	270	(resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (heat\$4 air\$3 gas\$4 age aging) near4 (treat\$4 harden\$3)	USPAT; EPO; JPO	OR	ON	2005/06/29 11:00
L7	0	(resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) same (treat\$4 harden\$3) and permanent\$2 near5 (elastic\$3 strength characteristic)	USPAT; EPO; JPO	OR	ON	2005/06/29 11:09
L8	0	(resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (treat\$4 harden\$3) with permanent\$2 near5 (elastic\$3 strength characteristic)	USPAT; EPO; JPO	OR	ON	2005/06/29 11:09
L9	1	(resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (treat\$4 harden\$3) with permanent\$2 with (elastic\$3 strength characteristic)	USPAT; EPO; JPO	OR	ON	2005/06/29 11:11
L10	128	(resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (treat\$4 harden\$3) with (elastic\$3 strength characteristic)	USPAT; EPO; JPO	OR	ON	2005/06/29 11:12
L11	45	"439"/\$ and (resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (treat\$4 harden\$3) near2 heat\$3	USPAT; EPO; JPO	OR	ON	2005/06/29 11:14

L12	24	"361"/\$ and (resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (treat\$4 harden\$3) near2 heat\$3	USPAT; EPO; JPO	OR	ON	2005/06/29 11:14
L13	24	"174"/\$ and (resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (treat\$4 harden\$3) near2 heat\$3	USPAT; EPO; JPO	OR	ON	2005/06/29 11:15
L14	44	"29"/\$ and (resilient sping\$3) near4 (conduct\$3 metal\$3 spring pin) with (contact pad land) and (treat\$4 harden\$3) near2 heat\$3	USPAT; EPO; JPO	OR	ON	2005/06/29 11:15